


Presse Bull



ARCHIMEDE 500



ARCHIMEDE 500

Caratteristiche Tecniche / General characteristics / Caractéristiques Générales		
Lunghezza interna cassa / Length of the internal case / Longueur interne de la caisse	mm	4800
Larghezza interna cassa aperta / Width of the internal case / Largeur interne de la caisse ouverte position écraseur	mm	2100
Altezza cassa / Height of the case / Hauteur interne de la caisse	mm	1600
Larghezza cassa chiusa (balla) / Size of the bale(Width) / Largeur interne de la caisse ouverte fin de course paquet	mm	900
Altezza cassa chiusa (balla) / Size of the bale(Height) / Hauteur de la caisse fermè	mm	700
Lunghezza balla / Slide for roll-off handling / Confection paquets par plancher et paroi mouvantes	mm	Variabile
Peso della macchina / Machine weight / Poids de la machine	kg	20.500
Dimensioni esterne / Press external dimensions / Dimensions extérieurs		
Lunghezza totale / Total length / Longueur totale	mm	7200
Larghezza totale / Total width / Largeur extérieur	mm	2450
Altezza cassa aperta / Total height / Hauteur couvercle ouvert	mm	2320
Altezza cassa chiusa / Total height when case is closed / Hauteur couvercle fermè	mm	2000
Motore Diesel / Diesel Engine / Moteur Diesel		
Costruttore / Manufacturer / Fabricant		FTP
Modello / Model / Modèle		Turbo intercooler
Potenza / Power / Puissance a dim 70020 à 2200 g / 1'	HP	175
Raffreddamento / Cooling / Refroidissement		acqua / water / eau
Quadro elettrico / Electric dashboard / Tableau de commande électrique		si / yes / oui
Velocità massima di rotazione / Top speed rotation / Vitesse de rotation maxi	rpm/1'	2500
Velocità minima di rotazione / Turns of exercise engine / Vitesse de rotation mini	rpm/1'	2200
Capacità serbatoio / Petrol tank capacity / Capacité réservoir gas oil	litri	100
Insonorizzazione motore / Soundproof engine bonnet		si / yes / oui
Circuito Idraulico / Hydraulic Circuit / Circuit Hydraulique		
Sistema idraulico / Pompes à pistons axiaux à cylindrée variable et à détection de charge / Axial piston pumps with variable displacement and load-sensing drive	réf. cm3	Sauer Danfoss 130 (2200 rpm)
Capacità totale circuito idraulico / Total capacity of hydraulic circuit / Capacité totale du circuit hydraulique	lt	1300
Capacità serbatoio / Capacity of hydraulic oil tank / Capacité réservoir hydraulique	lt	750
Optional		
RCS (Radio Control System) / (Remote Control System) / (Radio commande de contrôle à distance)		



Presse Bull srl
 via Gabriele Jannelli 220 | 80131 Napoli
 Tel. & Fax +39 081 5452063
 www.pressebull.it | info@pressebull.it

